

GAFA
SPECTACLE **595**



Aplicación Application	La gafa Climax 595-G ha sido diseñada para ofrecer una efectiva protección contra el riesgo de impacto de partículas de alta velocidad y baja energía y frente a la radiación solar (ámbito laboral). De esta forma la gafa es capaz de resistir el impacto pequeños proyectiles, tales como virutas de madera, metálicas y plásticas, trozos de tallos y ramas que se desprenden al utilizar maquinaria de jardinería, etc. La velocidad de los proyectiles debe ser inferior a 45 m/s. Su especial diseño limita mínimamente el ángulo de visión lateral y gracias a su neutralidad óptica y a su extremada ligereza permite un uso prolongado sin producir molestias al usuario. Climax 595-G spectacle have been designed to offer effective protection against the impact of high speed and low energy particles as well as sunlight (At work). Therefore, the goggles are able to withstand the impact of small projected particles, such as wood, metal or plastic chips or filings, pieces of stalks and plant twigs produced when using gardening machinery, etc. The speed of these particles should not exceed 45 m/s. Their special design offers minimal limitation of lateral vision and their optical neutrality and extreme lightness enables them to be worn for long periods without causing discomfort.			
Montura Frame	El frente, de una sola pieza, consiste en una tira de poliamida en forma de arco de color negro. Las patillas son tipo espátula extensibles. The front, made in one piece, has a black arch-shaped polyamide strip. The sidepieces are of the extendable spatula type.			
Ocular Eyepiece	Es de tipo panorámico, neutro, color humo, con un espesor nominal que varía entre 1.6 y 2.8. Las plaquetas de apoyo nasal son fijas, conformadas como resalte del propio ocular. It is panoramic, neutral and made of black polycarbonate, measuring nominally 1.6 to 2.8. The nose supports are fixed, made as an extension of the eyepiece itself.			
Marcado Marking	5 Protección frente a la radiación solar Protection against solar radiation	3.1 Grado de protección Protection degree	1 Clase óptica Optical class	FT Protección contra el riesgo de impacto de partículas de alta velocidad y baja energía a temperaturas extremas. Protection from risk of impact by low-energy, high-velocity particles at extreme temperatures.
				
Ensayos / Certificación CE Test / CE Certification	Certificación CE Normas: EN 166: 2001 EN 172: 1994 Reglamento (UE) 2016/425 CE Certification Norms: EN 166: 2001 EN 172: 1994 Regulation (EU) 2016/425			