

FICHA TÉCNICA / TECHNICAL INFORMATION

PIROX (ref. FF-001)

CE CAT III

Guante para bombero de intervención de Nomex con hilo de kevlar
Firefighter glove of Nomex and kevlar thread

EN 388



3 4 4 3

EN 659



DESCRIPCIÓN

Guante para bombero de intervención.
Cosido con hilo de kevlar.
Forro de nomex, recubrimiento de silicona y carbono.
Protección en nudillos.
Banda reflectante para mayor seguridad.
Membrana impermeable.
Puño elástico.
Banda de ajuste de kevlar en muñeca.

APLICACIONES

Trabajos con riesgo de calor y temperatura para la lucha contra incendios.

MARCAJE MECÁNICO

Abrasión:	Nivel 3
Corte por cuchilla:	Nivel 4
Desgarro:	Nivel 4
Perforación:	Nivel 3

ESPECIFICACIONES

Color:	Negro
Materiales:	Nomex y Kevlar
Tallas:	9, 10 & 11
Normativa:	EN 420, EN 388, EN 659

Este guante es conforme a las exigencias esenciales de Sanidad y Seguridad que le son de aplicación de acuerdo con el Real Decreto 1407/1992 y a sus modificaciones posteriores (O.M. del 16/05/1994, RD 159/1995 y O.M. de 20/02/1997) en base a la aplicación de los apartados que correspondan de las normas EN 420, EN 388 y EN 659.

Los valores indicados se basan en ensayos de laboratorio. 3L Internacional declina toda responsabilidad por el uso indebido de estos productos. En caso de duda consultar con nuestro servicio técnico.

12126/2 FT
17/01/17

DESCRIPTION

Intervention fire fighter glove.
Kevlar knitted.
Nomex liner, silicone and carbon reinforcements.
Knuckles protection.
Reflective strap.
Waterproof membrane.
Elastic cuff.
Kevlar Adjust strap in cuff.

APPLICATIONS

Works with heat and temperature risks for fire fighters

MECHANICAL RISKS

Abrasion:	Level 3
Blade cut:	Level 4
Tear:	Level 4
Puncture:	Level 3

SPECIFICATIONS

Colour:	Black
Materials:	Nómex and Kevlar
Sizes:	9, 10 & 11
Norms:	EN 420, EN 388, EN 659

This glove is in conformity with the essential requirements of Health and Security that are in application of agreement with the Royal decree 1407/1992 and further modifications (O.M. of 16/05/1994, RD 159/1995 and O.M. of 20/02/1997) on the basis of the application of the steps that fit with the norms EN 388, EN 420 and EN 659.

The values indicated are based in laboratory tests. 3L Internacional declines all responsibility for the inappropriate use of these products. In case of hesitation contact with our technical department.